

The Ash outdoor wall sconce is a modern take on the classic industrial-style light fixture. The Ash features a sleek metal shade and clear diffuser that creates a column of diffused light from under the shade. Ash wall sconces feature energy-efficient, fully dimmable integrated LED lighting. Available in four sizes (8", 10", 12", 16") and two finishes: Bronze and Charcoal.

### Outstanding protection against the elements:

- Marine-grade powder coat finishes
- Stainless Steel mounting hardware
- Impact-resistant, UV stabilized acrylic lensing
- IP-65 Rated

### SPECIFICATIONS

|                       |   |
|-----------------------|---|
| DELIVERED LUMENS      | 529 or 1114 with clear cylinder<br>323 or 675 with clear lens   |
| WATTS                 | 8 or 18   |
| VOLTAGE               | Universal 120-277V, with integral transient 2.5kV surge protection (driver)   |
| DIMMING               | 0-10, ELV   |
| LIGHT DISTRIBUTION    | Symmetric   |
| MOUNTING OPTIONS      | Wall  |
| PERFORMANCE OPTIONS   | Photocontrol / In-Line Fuse / Surge Protector   |
| CCT                   | 2700K or 3000K  |
| CRI                   | 90+   |
| COLOR BINNING         | 3 Step  |
| BUG RATING            | N/A   |
| DARK SKY              | Compliant (Lensed version only)   |
| WET LISTED            | IP65  |
| GENERAL LISTING       | ETL   |
| CALIFORNIA TITLE 24   | Can be used to comply with CEC 2016 Title 24 Part 6 for outdoor use. Registration with CEC Appliance Database not required. |
| START TEMP            | -30°C   |
| FIELD SERVICEABLE LED | Yes   |
| CONSTRUCTION          | Aluminum  |
| HARDWARE              | Stainless Steel   |
| FINISH                | Marine Grade Powder Coat  |
| LED LIFETIME          | L70; 70,000 Hours   |
| WARRANTY*             | 5 Years   |

\* Visit [techlighting.com](http://techlighting.com) for specific warranty limitations and details.



ASH 10  
shown in bronze/clear cylinder




ASH 10  
shown in charcoal/clear lens

### ORDERING INFORMATION

| 7000WASH | CRI / CCT                      | LENGTH | LENS                             | FINISH                 | VOLTAGE                    | DISTRIBUTION | OPTIONS   |
|----------|--------------------------------|--------|----------------------------------|------------------------|----------------------------|--------------|---|
| L927     | LED LO-OUTPUT<br>90 CRI, 2700K | 10 10" | C CLEAR CYLINDER<br>D CLEAR DOME | Z BRONZE<br>H CHARCOAL | UNV 120V-277V<br>UNIVERSAL | S SYMMETRIC  | NONE<br>PC BUTTON PHOTOCONTROL<br>LF IN-LINE FUSE<br>SP SURGE PROTECTION<br>PCLF BUTTON PHOTOCONTROL & IN-LINE FUSE<br>PCSP BUTTON PHOTOCONTROL & SURGE PROTECTION<br>LFSP IN-LINE FUSE & SURGE PROTECTION<br>PCLFSP BUTTON PHOTOCONTROL, IN-LINE FUSE & SURGE PROTECTION |
| H927     | LED HI-OUTPUT<br>90 CRI, 2700K |        |                                  |                        |                            |              |   |
| L930     | LED LO-OUTPUT<br>90 CRI, 3000K |        |                                  |                        |                            |              |   |
| H930     | LED HI-OUTPUT<br>90 CRI, 3000K |        |                                  |                        |                            |              |   |

# ASH 10 WALL SCONCE



Ash 10

## PHOTOMETRICS\*

\*For latest photometrics, please visit [www.techlighting.com/OUTDOOR](http://www.techlighting.com/OUTDOOR)

### ASH 10

|                     |                |
|---------------------|----------------|
| Total Lumen Output: | 529 or 1114    |
| Total Power:        | 8 or 18        |
| Luminaire Efficacy: | 66 or 62       |
| Color Temp:         | 2700K or 3000K |
| CRI:                | 90             |
| BUG Rating:         | N/A            |

## PROJECT INFO

| FIXTURE TYPE & QUANTITY | JOB NAME & INFO | NOTES |
|-------------------------|-----------------|-------|
| <hr/>                   | <hr/>           | <hr/> |
| <hr/>                   | <hr/>           | <hr/> |



GENERATION BRANDS  
7400 Linder Avenue, Skokie, Illinois 60077

T 847.410.4400 F 847.410.4500



© 2017 Tech Lighting, L.L.C. All rights reserved. The "Tech Lighting" graphic is a registered trademark of Tech Lighting, L.L.C. Tech Lighting reserves the right to change specifications for product improvements without notification.