

The Aspen outdoor wall sconce creates an elegant elongated column of beautifully diffused light. The Aspen is available in four sizes (8", 15", 26", 36") to meet architectural scale; ideal for way-finding and general outdoor illumination. The Aspen features energy-efficient, fully dimmable integrated LED lamping. Available in two finishes: Bronze and Charcoal.

High quality LM80-tested LEDs

for consistent long-life performance and color

Outstanding protection against the elements:

- Marine-grade powder coat finishes
- Stainless Steel mounting hardware
- Impact-resistant, UV stabilized frosted acrylic lensing
- IP-65 Rated

SPECIFICATIONS

| | |
|-----------------------|---|
| DELIVERED LUMENS | 1123 |
| WATTS | 18.8 |
| VOLTAGE | Universal 120-277V, with integral transient 2.5kV surge protection (driver) |
| DIMMING | 0-10, ELV |
| LIGHT DISTRIBUTION | Symmetric |
| MOUNTING OPTIONS | Wall |
| PERFORMANCE OPTIONS | In-Line Fuse / Surge Protector |
| CCT | 3000K |
| CRI | 90+ |
| COLOR BINNING | 3 Step |
| BUG RATING | N/A |
| DARK SKY | Non-compliant |
| WET LISTED | IP65 |
| GENERAL LISTING | ETL |
| CALIFORNIA TITLE 24 | Can be used to comply with CEC 2016 Title 24 Part 6 for outdoor use. Registration with CEC Appliance Database not required. |
| START TEMP | -30°C |
| FIELD SERVICEABLE LED | Yes |
| CONSTRUCTION | Aluminum |
| HARDWARE | Stainless Steel |
| FINISH | Marine Grade Powder Coat |
| LED LIFETIME | L70; 70,000 Hours |
| WARRANTY* | 5 Years |



ASPEN 15
shown in bronze




ASPEN 15
shown in charcoal

* Visit techlighting.com for specific warranty limitations and details.

ORDERING INFORMATION

| 7000WASP | CRI / CCT | LENGTH | LENS | FINISH | VOLTAGE | DISTRIBUTION | OPTIONS |
|----------|-------------------|--------|-----------|------------------------|-------------------------|--------------|--|
| | 930 90 CRI, 3000K | 15 15" | D DIFFUSE | Z BRONZE H CHARCOAL | UNV 120V-277V UNIVERSAL | S SYMMETRIC | NONE LF IN-LINE FUSE SP SURGE PROTECTION LFSP IN-LINE FUSE & SURGE PROTECTION |



Aspen 15

PHOTOMETRICS*

*For latest photometrics, please visit www.techlighting.com/OUTDOOR

ASPEN 15

| | |
|---------------------|-------|
| Total Lumen Output: | 1123 |
| Total Power: | 18.8 |
| Luminaire Efficacy: | 60 |
| Color Temp: | 3000K |
| CRI: | 90 |
| BUG Rating: | N/A |

PROJECT INFO

| FIXTURE TYPE & QUANTITY | JOB NAME & INFO | NOTES |
|-------------------------|-----------------|-------|
| | | |
| | | |

