


# LOW - VOLTAGE HEADS

## Brim Head



### DESCRIPTION

The ultra-slim Brim spot head light from Tech Lighting features field-changeable optics and an optional decorative glass collar. The latest advances in technology deliver an extremely powerful LED head without the bulk typically needed to conceal a driver and manage thermal performance. Includes field replaceable 7 watt, 855 delivered lumen, 2700K or 3000K field replaceable LED module Dimmable with low-voltage electronic or magnetic dimmer (based on the transformer) Choice of 20°, 30° or 40° field changeable optics. Integrated lens holder accommodates up to 2 lenses or louvers (sold separately) As a general rule when using the Brim head, we do not recommend using greater than 33% of the maximum wattage specified for the low voltage transformer due to inrush current requirements. For assistance in calculations, please contact Technical Support.



### INSTALLATION

Socket terminates with FreeJack male connector, which may be installed into a system connector. Elements ordered with a system prefix include a connector for that system. For use on T-TRAK, order FreeJack version and T-TRAK FreeJack Connector (sold separately).

### WEIGHT

0.23lb / 0.1kg ±



### ORDERING INFORMATION

700	SYSTEM	BRM	COLOR TEMP	BEAM SPREAD	LENGTH (A)	COLOR	FINISH
FJ	FREEJACK		927 90 CRI 2700K	20 20°	05 5"	C CLEAR	B BLACK
MP	MONOPOINT		930 90 CRI 3000K	30 30°	08 7.76"	K TRANSPARENT SMOKE	S SATIN NICKEL
MO	MONORAIL			40 40°	14 13.76"		
MO2	TWO-CIRCUIT MONORAIL						

Note: MP includes 4 Round Flush Canopy.

When installing LED option on MO2 only magnetic transformers may be used.



**TECH LIGHTING®**  
 7400 Linder Avenue T 847.410.4400  
 Skokie, Illinois 60077 F 847.410.4500

**Tech Lighting, L.L.C.**

700 \_\_\_\_ BRM \_\_\_\_\_

FIXTURE TYPE: \_\_\_\_\_

JOB NAME: \_\_\_\_\_

NOTES: \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_