


LOW - VOLTAGE HEADS

Brim Head

DESCRIPTION

The ultra-slim Brim spot head light from Tech Lighting features field-changeable optics and an optional decorative glass collar. The latest advances in technology deliver an extremely powerful LED head without the bulk typically needed to conceal a driver and manage thermal performance. Includes field replaceable 7 watt, 855 delivered lumen, 2700K or 3000K field replaceable LED module Dimmable with low-voltage electronic or magnetic dimmer (based on the transformer) Choice of 20°, 30° or 40° field changeable optics. Integrated lens holder accommodates up to 2 lenses or louvers (sold separately) As a general rule when using the Brim head, we do not recommend using greater than 33% of the maximum wattage specified for the low voltage transformer due to inrush current requirements. For assistance in calculations, please contact Technical Support.



INSTALLATION

Socket terminates with FreeJack male connector, which may be installed into a system connector. Elements ordered with a system prefix include a connector for that system. For use on T-TRAK, order FreeJack version and T-TRAK FreeJack Connector (sold separately).

WEIGHT

0.23lb / 0.1kg ±



ORDERING INFORMATION

700	SYSTEM	BRM	COLOR TEMP	BEAM SPREAD	LENGTH (A)	COLOR	FINISH
FJ	FREEJACK		927 90 CRI 2700K	20 20°	05 5"	C CLEAR	B BLACK
MP	MONOPOINT		930 90 CRI 3000K	30 30°	08 7.76"	K TRANSPARENT SMOKE	S SATIN NICKEL
MO	MONORAIL			40 40°	14 13.76"		
MO2	TWO-CIRCUIT MONORAIL						

Note: MP includes 4 Round Flush Canopy.

When installing LED option on MO2 only magnetic transformers may be used.



TECH LIGHTING®
 7400 Linder Avenue T 847.410.4400
 Skokie, Illinois 60077 F 847.410.4500

Tech Lighting, L.L.C.

700 ____ BRM _____

FIXTURE TYPE: _____

JOB NAME: _____

NOTES: _____
