

LOW - VOLTAGE PENDANTS

Essex Pendant

DESCRIPTION

Individually slumped glass panels joined with a metal frame. Includes low-voltage, 50 watt halogen bi-pin lamp or 8 watt, 300 delivered lumen, 3000K, replaceable SORAA® LED module and six feet of field-cutttable cable. Dimmable with low-voltage electronic or magnetic dimmer (based on transformer). Works with SORAA.

INSTALLATION

Socket terminates with FreeJack male connector, which may be installed into a system connector. Elements ordered with a system prefix include a connector for that system. ForFor Kable Lite due to weight.

ACCESSORIES & OPTICAL CONTROLS


Line-voltage Swag Hook, SORAA® LED Bi-Pin Replacement Pendant Module, Swag Hook

WEIGHT

2.1lb / 0.95kg ±



beach amber



beach amber



sand

ORDERING INFORMATION

700	SYSTEM	ESX	COLOR	FINISH	LAMP
FJ	FREEJACK		A BEACH AMBER	Z ANTIQUE BRONZE	12 VOLT HALOGEN
MP	MONOPOINT		S SAND	S SATIN NICKEL	-LEDS830 12 VOLT LED 80 CRI 3000K
MO	MONORAIL		W SURF WHITE		-24 24 VOLT HALOGEN
MO2	TWO-CIRCUIT MONORAIL				

Note: MP includes 4" Round Flush Canopy. Note: MP includes 4 Round Flush Canopy.



TECH LIGHTING®
 7400 Linder Avenue T 847.410.4400
 Skokie, Illinois 60077 F 847.410.4500
Tech Lighting, L.L.C.

700 ____ ESX ____

FIXTURE TYPE: _____

JOB NAME: _____

NOTES: _____



©2017 Tech Lighting, L.L.C. All Rights Reserved. The "Tech Lighting" graphic is a registered trademark of Tech Lighting, L.L.C. Tech Lighting reserves the right to change specifications for product improvements without notification.