

LOW-VOLTAGE PENDANTS

Firefrost Pendant

DESCRIPTION

Murano glass with frosted or case glass interior. Includes low-voltage, 50 watt halogen bi-pin lamp or 8 watt, 300 delivered lumen, 3000K, replaceable SORAA® LED module and six feet of field-cuttable cable. Dimmable with low-voltage electronic or magnetic dimmer (based on transformer). Works with SORAA.

INSTALLATION

Socket terminates with FreeJack male connector, which may be installed into a system connector. Elements ordered with a system prefix include a connector for that system. For use on T~TRAK, order FreeJack version and T~TRAK FreeJack Connector (sold separately).

ACCESSORIES & OPTICAL CONTROLS


SORAA® LED Bi-Pin Replacement Pendant Module, Swag Hook

WEIGHT

2lb / 0.91kg ±



chartreuse



amber



chartreuse



cobalt



red



white

ORDERING INFORMATION

700	SYSTEM	FIRF	COLOR	FINISH	LAMP
FJ	FREEJACK		A AMBER	Z ANTIQUE BRONZE	12 VOLT HALOGEN
KL	KABLE LITE		H CHARTREUSE	C CHROME	-LEDS930 12 VOLT LED 90 CRI 3000K
MP	MONOPOINT		B COBALT	S SATIN NICKEL	-24 24 VOLT HALOGEN
MO	MONORAIL		R RED		
MO2	TWO-CIRCUIT MONORAIL		W WHITE		

Note: Note: MP includes 4" Round Flush Canopy.

Antique Bronze is not available for Kable Lite

Chrome not offered on Monorail & Two-Circuit Monorail.



700 ____ FIRF _____

FIXTURE TYPE: _____

JOB NAME: _____

NOTES: _____



©2017 Tech Lighting, L.L.C. All Rights Reserved. The "Tech Lighting" graphic is a registered trademark of Tech Lighting, L.L.C. Tech Lighting reserves the right to change specifications for product improvements without notification.