


Helios LED

ARCHITECTURAL HEAD



Power Consumption:	Initial 6 watts
Color Temperature:	3000° K
Lumens:	350 net lumens
Lumens/Watt:	55 lms / watt
Color Rendering Index:	>85 CRI
Rated Average Life:	>30,000 hours to L70
Center Beam	
Candle Power:	25° - 748; 40° - 550
Dimming:	10%
Warranty:	5 years



Socket terminates with FreeJack male connector, which may be installed into a system connector. Elements ordered with a system prefix include a connector for that system.

DESCRIPTION

6 watt directional LED head. It is easily field replaceable with the screw-in base specifically designed for our LED module. The heat sink remains with the fixture minimizing any waste at the end of the lamp module life. Head rotates 360° and pivots 260° to direct the beam. Accessories in myriad styles and colors allow you to create the ideal custom LED fixture (accessories required; sold separately).

SYSTEM

Available for FreeJack, MonoRail and Wall MonoRail. For use on T~TRAK, order FreeJack version and T~TRAK FreeJack Connector (sold separately).

COLOR

None

FINISH

Antique bronze, satin nickel

LAMP

12 Volt LED 3000K

ACCESSORIES AND OPTICAL CONTROLS

Accessory required. Compatible accessories and optical controls (sold separately): Cone, Cone Onyx, Dichroic, Firebird, Martini, Prism, Round or Soda Glass Shield; Bell, Belladonna, Lil Egypt, Meteorite, Scavo, Sugar, Taza or Tinkerbell.

WEIGHT

4.11 lb

ORDERING INFORMATION

700	SYSTEM	HEL	BEAM SPREAD	LENGTH (A)	FINISH	-LED
	FJ	FREEJACK	25 25°	03 3"	Z	ANTIQUE BRONZE
	MO	MONORAIL	40 40°	06 6"	S	SATIN NICKEL
	WMO	WALL MONORAIL		12 12"		
				18 18"		
				24 24"		



7400 Linder Avenue T 847.410.4400
 Skokie, Illinois 60077 F 847.410.4500
www.techlighting.com

700 _____ HEL _____ -LED

FIXTURE TYPE: _____

JOB NAME: _____

