


# LOW - VOLTAGE HEADS

## ISO Head

### DESCRIPTION

16 watt, 850+ lumen directional LED head. The precision lines of the heat sink peak through the sleek outer housing creating a look that speaks to the functional performance of the luminaire. The LED is easily field-replaceable and upgradeable due to the solderless connector. The heat sink remains with the fixture minimizing any waste at the end of the lamp module's life. The head rotates 360° and pivots 90° to direct the beam. Integrated lens holder accommodates one MR16 size lens or louver (sold separately). As a general rule when using the ISO Head, we do not recommend using greater than 33% of the maximum wattage specified for the low-voltage transformer due to the inrush current requirements. For assistance in calculations, please contact our Technical Support Department.



### ACCESSORIES & OPTICAL CONTROLS

Dichroic Lens, Eggcrate Louver

### WEIGHT

1.58lb / 0.72kg ±



satin nickel



white

### ORDERING INFORMATION

700	SYSTEM	ISO	COLOR TEMP	BEAM SPREAD	LENGTH (A)	FINISH	LAMP
FJ	FREEJACK		827 80 CRI 2700K	20 20°	03 3"	S SATIN NICKEL	-LED LED
MP	MONOPOINT		830 80 CRI 3000K	30 30°	06 6"	W WHITE	
MO	MONORAIL				12 12"		
MO2	TWO-CIRCUIT MONORAIL		930 90 CRI 3000K	50 50°	18 18"		

Note: MP includes 4" Round Flush Canopy.

When installing LED option on MO2 only magnetic transformers may be used. Due to weight capacity issues, do not exceed a 45 degree angle.



**TECH LIGHTING®**

7400 Linder Avenue  
Skokie, Illinois 60077

T 847.410.4400  
F 847.410.4500

Tech Lighting, L.L.C.

700 \_\_\_\_ ISO \_\_\_\_\_

FIXTURE TYPE: \_\_\_\_\_

JOB NAME: \_\_\_\_\_

NOTES: \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_



©2017 Tech Lighting, L.L.C. All Rights Reserved. The "Tech Lighting" graphic is a registered trademark of Tech Lighting, L.L.C. Tech Lighting reserves the right to change specifications for product improvements without notification.