

LOW - VOLTAGE HEADS

K-Rae Head



DESCRIPTION

More than just a head, this unique fixture integrates the uncompromising light quality of our Unilume LED Micro Channel (which utilizes remote phosphor LED technology) with the versatility of Kable Lite. Available in two parallel length options and one perpendicular length option (consult factory for custom lengths). Each head pivots 360° and can be mounted up or down for easy control of light making it ideal for direct and indirect general illumination, wall wash and display applications. When used in conjunction with other low-voltage heads and pendants, the K-Rae offers incredible flexibility to layer light throughout a space. 7.8 watts/ft, 600 net lumens/ft.



WEIGHT

0.19-0.75lb / 0.09-0.34kg ±



k-rae head

ORDERING INFORMATION

700KLRAER	CRI	COLOR TEMP	LENGTH (A)	CABLE SEPARATION	FINISH	LAMP
8	80 CRI	24 2400K	05 5"	05 5.5"	S SATIN NICKEL	-LED LED
		830 80 CRI 3000K	12 12"			
		835 80 CRI 3500K	24 24"			
		840 80 CRI 4000K				
		930 90 CRI 3000K				



TECH LIGHTING®

7400 Linder Avenue T 847.410.4400
 Skokie, Illinois 60077 F 847.410.4500

Tech Lighting, L.L.C.

700KLRAER _____

FIXTURE TYPE: _____

JOB NAME: _____

NOTES: _____



©2017 Tech Lighting, L.L.C. All Rights Reserved. The "Tech Lighting" graphic is a registered trademark of Tech Lighting, L.L.C. Tech Lighting reserves the right to change specifications for product improvements without notification.