

LOW - VOLTAGE PENDANTS

Masque Pendant



DESCRIPTION

A simple yet sophisticated look is created by a one-piece blown glass shade with a meticulously painted crown which cleverly hides the LED light source. Includes 4.5 watt, 280 net lumen, 3000K replaceable LED module with diffuser. Ships with six feet of field-cutable suspension cable. Dimmable with low-voltage electronic dimmer (based on transformer).

INSTALLATION

Socket terminates with FreeJack male connector, which may be installed into a system connector. Elements ordered with a system prefix include a connector for that system. For use on T~TRAK, order FreeJack version and T~TRAK FreeJack Connector (sold separately).

ACCESSORIES & OPTICAL CONTROLS

SORAA® LED Bi-Pin Replacement Pendant Module, Swag Hook

WEIGHT

2.48lb / 1.12kg ±



smoke/black



clear / white



smoke / black



smoke / gray

ORDERING INFORMATION

700	SYSTEM	MSQ	COLOR	FINISH	LAMP
FJ	FREEJACK		CW CLEAR/WHITE	S SATIN NICKEL	-LED 12 VOLT LED 80 CRI 3000K
MP	MONOPOINT		KB SMOKE/BLACK		-24 24 VOLT HALOGEN
MO	MONORAIL		KY SMOKE/GRAY		
MO2	TWO-CIRCUIT MONORAIL				

Note: MP includes 4" Round Flush Canopy.



7400 Linder Avenue T 847.410.4400
Skokie, Illinois 60077 F 847.410.4500

Tech Lighting, L.L.C.

700 ____ MSQ ____

FIXTURE TYPE: _____

JOB NAME: _____

NOTES: _____



©2017 Tech Lighting, L.L.C. All Rights Reserved. The "Tech Lighting" graphic is a registered trademark of Tech Lighting, L.L.C. Tech Lighting reserves the right to change specifications for product improvements without notification.