


Rigid Standoff



Shown approximately 15% actual size.



mo_rigid_standoff_spec.pdf

DESCRIPTION

The field-cutable rigid standoff is recommended for curvy runs or runs with heavier Heads, Pendants or Functional art, such as glass pendants. Rigid standoffs are compatible with various power feed options: Use the chart below to determine the appropriate standoff for your run.

FINISH

Antique bronze, chrome, satin nickel.

WEIGHT

0.25-2.55 lb./0.11-1.16 kg. ±

COMPATIBLE STANDOFF

LENGTH	USED WITH
2" (1.9")*	- Remote transformer with canopy - Flush transformer 60w - Recessed can transformer
3" (3.6")*	- Surface transformer 60w, 75w, 100w, 150w - Canopy with 3" power extender
4" (4.8")*	- Surface transformer 300w
5" (5.8")*	- Surface transformer 600w
6"*	- Canopy with 6" power extender
12"*	- Canopy with 12" power extender
24"*	- Canopy with 24" power extender
36"*	- Canopy with 36" power extender
48"*	- Canopy with 48" power extender
96"*	- Canopy with 96" power extender

*Actual length from ceiling to top of rail.

ORDERING INFORMATION

700MOS	LENGTH (A)	FINISH
02	2" (1.9")	Z ANTIQUE BRONZE
03	3" (3.6")	C CHROME
04	4" (4.8")	S SATIN NICKEL
05	5" (5.8")	
06	6"	
12	12"	
24	24"	
36	36"	
48	48"	
96	96"	

*Actual length from ceiling to top of rail.



TECH LIGHTING®

7400 Linder Avenue T 847.410.4400
Skokie, Illinois 60077 F 847.410.4500

www.techlighting.com

700MOS _____

FIXTURE TYPE: _____

JOB NAME: _____

