

LOW - VOLTAGE PENDANTS

Nebbia Pendant LED SORAA T20

DESCRIPTION

Hand-blown glass with an elegantly fused glass wrap. Includes low-voltage, 50 watt halogen bi-pin lamp or 8 watt, 300 delivered lumen, 3000K, replaceable SORAA® LED module and six feet of field-cutable cable. Dimmable with low-voltage electronic or magnetic dimmer (based on transformer) Works with SORAA.

INSTALLATION


Socket terminates with FreeJack male connector, which may be installed into a system connector. Elements ordered with a system prefix include a connector for that system.

ACCESSORIES & OPTICAL CONTROLS

SORAA® LED Bi-Pin Replacement Pendant Module

WEIGHT

2lb / 0.91kg ±



amber



amber



smoke



white

ORDERING INFORMATION

700	SYSTEM	NEBL	COLOR	FINISH	LAMP
FJ	FREEJACK		A AMBER	Z ANTIQUE BRONZE	12 VOLT HALOGEN (T20)
MP	MONOPOINT		K SMOKE	S SATIN NICKEL	-LEDS930 12 VOLT LED 90 CRI 3000K (T20/T24)
MO	MONORAIL		W WHITE		-24 24 VOLT HALOGEN
MO2	TWO-CIRCUIT MONORAIL				

Note: MP includes 4" Round Flush Canopy. Note: MP includes 4 Round Flush Canopy.

When installing LED option on MO2 only magnetic transformers may be used.

TECH LIGHTING®
 7400 Linder Avenue T 847.410.4400
 Skokie, Illinois 60077 F 847.410.4500

Tech Lighting, L.L.C.

700 ____ NEBL ____

FIXTURE TYPE: _____

JOB NAME: _____

NOTES: _____
