

With a minimalist modern approach in mind, the Neutrino compact outdoor sconce directs the LED light down, minimizing wasted light and glare. Clean lines and a sloped roofline accent-but don't detract-from architectural surroundings.

Outstanding protection against the elements:

- Powder coat finishes
- Stainless Steel mounting hardware
- Impact-resistant, UV stabilized frosted acrylic lensing

SPECIFICATIONS

DELIVERED LUMENS	463
WATTS	14
VOLTAGE	120V
DIMMING	ELV
LIGHT DISTRIBUTION	Symmetric
MOUNTING OPTIONS	Wall
CCT	Warm Color Dimming (3000K - 2200K)
CRI	90
COLOR BINNING	3-Step
BUG RATING	N/A
DARK SKY	Compliant
WET LISTED	IP65
GENERAL LISTING	ETL, ADA
CALIFORNIA TITLE 24	Can be used to comply with CEC 2016 Title 24 Part 6 for outdoor use. Registration with CEC Appliance Database not required.
START TEMP	-30°C
FIELD SERVICEABLE LED	Yes
CONSTRUCTION	Aluminum
HARDWARE	Stainless Steel
FINISH	Powder Coat
LED LIFETIME	L70; 70,000 hours
WARRANTY*	5 years
WEIGHT	2.5 lbs.



NEUTRINO
shown in bronze




NEUTRINO
shown in silver

* Visit techlighting.com for specific warranty limitations and details.

ORDERING INFORMATION

700WSNTRN	FINISH	LAMP
Z	BRONZE	LEDLW LED 90CRI, 3000K-2200K, 120V
I	SILVER	



Neutrino

PHOTOMETRICS*

*For latest photometrics, please visit www.techlighting.com/OUTDOOR

NEUTRINO

Total Lumen Output:	463
Total Power:	14.4
Luminaire Efficacy:	32
Color Temp:	Warm Color Dimming (3000K - 2200K)
CRI:	90
BUG Rating:	N/A

PROJECT INFO

FIXTURE TYPE & QUANTITY	JOB NAME & INFO	NOTES