

The contemporary, hexagonal shape of the Root outdoor wall sconce creates a column of diffused LED light aimed for downward illumination of outdoor passageways or paths. This geometrically inspired light fixture can be installed with an open aperture, optional weaved wire mesh or perforated metal diffusers for heightened visual interest. Root wall sconces feature energy-efficient, fully dimmable integrated LED lamping. Available in two sizes (15", 20") and two finishes: Bronze and Charcoal.


Outstanding protection against the elements:

- Marine-grade powder coat finishes
- Impact-resistant, UV stabilized frosted acrylic lensing
- IP-65 Rated

SPECIFICATIONS

DELIVERED LUMENS	308
WATTS	15
VOLTAGE	Universal 120-277V, with integral transient 2.5kV surge protection (driver)
DIMMING	0-10, ELV
LIGHT DISTRIBUTION	Symmetric
OPTICS	40°
MOUNTING OPTIONS	Wall
PERFORMANCE OPTIONS	Photocontrol / Surge Protector
CCT	3000K
CRI	90+
COLOR BINNING	3 Step
BUG RATING	B1-U0-G0
DARK SKY	Compliant
WET LISTED	IP65
GENERAL LISTING	ETL
CALIFORNIA TITLE 24	Can be used to comply with CEC 2016 Title 24 Part 6 for outdoor use. Registration with CEC Appliance Database not required.
START TEMP	-30°C
FIELD SERVICEABLE LED	Yes
CONSTRUCTION	Aluminum
HARDWARE	Stainless Steel
FINISH	Marine Grade Powder Coat
LED LIFETIME	L70; 70,000 Hours
WARRANTY*	5 Years
WEIGHT	8 lbs.

* Visit techlighting.com for specific warranty limitations and details.



ROOT 20
shown in charcoal
(wire mesh shown)




ROOT 20
shown in bronze

ORDERING INFORMATION

7000WROT	CRI / CCT	LENGTH	LENS	FINISH	VOLTAGE	DISTRIBUTION	OPTIONS
930	90 CRI, 3000K	20 20"	C CLEAR	Z BRONZE H CHARCOAL	UNV 120V-277V UNIVERSAL	S SYMMETRIC	NONE PC BUTTON PHOTOCONTROL SP SURGE PROTECTION PCSP BUTTON PHOTOCONTROL & SURGE PROTECTION

ROOT 20 WALL SCONCE




Root 20

PHOTOMETRICS*

*For latest photometrics, please visit www.techlighting.com/OUTDOOR

ROOT 20

Total Lumen Output: 308
 Total Power: 15
 Luminaire Efficacy: 20
 Color Temp: 3000K
 CRI: 90
 BUG Rating: B1-U0-G0



PROJECT INFO

FIXTURE TYPE & QUANTITY

JOB NAME & INFO

NOTES



GENERATION BRANDS
 7400 Linder Avenue, Skokie, Illinois 60077

T 847.410.4400 F 847.410.4500



© 2017 Tech Lighting, L.L.C. All rights reserved. The "Tech Lighting" graphic is a registered trademark of Tech Lighting, L.L.C. Tech Lighting reserves the right to change specifications for product improvements without notification.