

LOW - VOLTAGE HEADS

Spot Head

DESCRIPTION

Classic head rotates 360° around stem, pivots 290°. Can hold one lens or louver (sold separately). Low-voltage, MR16 lamp of up to 50 watts (not included). Works with SORAA.

INSTALLATION


Socket terminates with FreeJack male connector, which may be installed into a system connector. Elements ordered with a system prefix include a connector for that system.

ACCESSORIES & OPTICAL CONTROLS

Dichroic Lens, Eggcrate Louver

WEIGHT

0.84lb / 0.38kg ±



straight



with eggcrate louver

ORDERING INFORMATION

700 SYSTEM	SPT6	LENGTH (A)	FINISH
FJ	FREEJACK	04 4.5"	S SATIN NICKEL
MP	MONOPOINT	06 6"	
MO	MONORAIL	12 12"	
MO2	TWO-CIRCUIT MONORAIL	18 18"	
WMO	WALL MONORAIL		

Note: MP includes 4" Round Flush Canopy.



TECH LIGHTING®

7400 Linder Avenue
Skokie, Illinois 60077

T 847.410.4400
F 847.410.4500

Tech Lighting, L.L.C.

700 ____ SPT6 ____

FIXTURE TYPE: _____

JOB NAME: _____

NOTES: _____



©2017 Tech Lighting, L.L.C. All Rights Reserved. The "Tech Lighting" graphic is a registered trademark of Tech Lighting, L.L.C. Tech Lighting reserves the right to change specifications for product improvements without notification.