

Understated modern design characterizes Tegel outdoor LED wall sconces. Providing well-controlled up and down lighting, or down light only, these wall sconces provide accent and ambient illumination. The option of three finish choices ensures this design profile successfully blends with all architectural aesthetics.

### High quality LM80-tested LEDs

for consistent long-life performance and color

### Outstanding protection against the elements:

- Marine-grade powder coat finishes
- Stainless Steel mounting hardware
- Impact-resistant, UV stabilized frosted acrylic lensing

### Up light and down light options, with 10° and 36° beam spread options

## SPECIFICATIONS

|                       |   |
|-----------------------|---|
| DELIVERED LUMENS      | 2419 Up-Downlight / 1212 Downlight  |
| WATTS                 | 29.9 Up-Downlight / 15.6 Downlight  |
| VOLTAGE               | Universal 120-277V, with integral transient 2.5kV surge protection (driver) |
| DIMMING               | 0-10, ELV   |
| LIGHT DISTRIBUTION    | Symmetric Up/Down Lighting, or Down Only                                    |
| MOUNTING OPTIONS      | Wall  |
| OPTICS                | 10° and 36°   |
| PERFORMANCE OPTIONS   | Photocontrol / In-Line Fuse / Surge Protector                               |
| CCT                   | 3000K or 4000K  |
| CRI                   | 80+   |
| COLOR BINNING         | 3 Step  |
| BUG RATING            | Up-Downlight B1-U5-G0 / Downlight B1-U0-G0                                  |
| DARK SKY              | Compliant (Downlight)   |
| WET LISTED            | IP65  |
| GENERAL LISTING       | ETL, Title 24   |
| START TEMP            | -30°C   |
| FIELD SERVICEABLE LED | Yes   |
| CONSTRUCTION          | Aluminum  |
| HARDWARE              | Stainless Steel   |
| FINISH                | Marine Grade Powder Coat  |
| LED LIFETIME          | L70; 70,000 Hours   |
| WARRANTY*             | 5 Years   |

\* Visit [techlighting.com](http://techlighting.com) for specific warranty limitations and details.



TEGEL 18  
shown in bronze

TEGEL 18  
shown in charcoal


TEGEL 18  
shown in gray

## ORDERING INFORMATION

| 700OWTEG | CRI/CCT                  | LENGTH        | BEAM SPREAD*              | LENS           | FINISH            | FUNCTION                    | VOLTAGE              | OPTIONS  |
|----------|--------------------------|---------------|---------------------------|----------------|-------------------|-----------------------------|----------------------|--|
|          | <b>830</b> 80 CRI, 3000K | <b>18</b> 18" | <b>N</b> 10° NARROW       | <b>C</b> CLEAR | <b>Z</b> BRONZE   | <b>DO</b> DOWNLIGHT ONLY    | <b>UNV</b> 120V-277V | <b>PC</b> NONE   |
|          | <b>840</b> 80 CRI, 4000K |               | <b>W</b> 36° WIDE         |                | <b>H</b> CHARCOAL | <b>UD</b> UPLIGHT/DOWNLIGHT |                      | <b>BF</b> BUTTON PHOTOCONTROL                                      |
|          |                          |               | <b>NN</b> 10° UP AND DOWN |                | <b>Y</b> GRAY     |                             |                      | <b>LF</b> IN-LINE FUSE   |
|          |                          |               | <b>WW</b> 36° UP AND DOWN |                |                   |                             |                      | <b>SP</b> SURGE PROTECTION   |
|          |                          |               | <b>NW</b> 10° AND 36°     |                |                   |                             |                      | <b>PCLF</b> BUTTON PHOTOCONTROL & IN-LINE FUSE                     |
|          |                          |               |                           |                |                   |                             |                      | <b>PCSP</b> BUTTON PHOTOCONTROL & SURGE PROTECTION                 |
|          |                          |               |                           |                |                   |                             |                      | <b>LFSP</b> IN-LINE FUSE & SURGE PROTECTION                        |
|          |                          |               |                           |                |                   |                             |                      | <b>PCLFSP</b> BUTTON PHOTOCONTROL, IN-LINE FUSE & SURGE PROTECTION |

\*N, W = DOWNLIGHT ONLY (DO); NN, WW, NW = UP AND DOWNLIGHT ONLY (UD)

# TEGEL 18 WALL SCONCE



Tegel 18

## PHOTOMETRICS\*


\*For latest photometrics, please visit [www.techlighting.com/OUTDOOR](http://www.techlighting.com/OUTDOOR)

### TEGEL 18 UP/DOWN


Total Lumen Output: 2419  
 Total Power: 29.9  
 Luminaire Efficacy: 80.6  
 Color Temp: 3000K  
 CRI: 80+  
 BUG Rating: B1-U5-G0

### TEGEL 18 DOWN

Total Lumen Output: 1212  
 Total Power: 15.6  
 Luminaire Efficacy: 77.7  
 Color Temp: 3000K  
 CRI: 80+  
 BUG Rating: B1-U0-G0



Up-downlight



Downlight

## PROJECT INFO

FIXTURE TYPE & QUANTITY

JOB NAME & INFO

NOTES

---



---



---



---



---



---



© 2016 Tech Lighting, L.L.C. All rights reserved. The "Tech Lighting" graphic is a registered trademark of Tech Lighting, L.L.C. Tech Lighting reserves the right to change specifications for product improvements without notification.



GENERATION BRANDS  
 7400 Linder Avenue, Skokie, Illinois 60077  
 T 847.410.4400 F 847.410.4500