

# MONORAIL 4" ROUND POWER FEED CANOPY LOW-PROFILE DUAL-FEED



## PRODUCT FEATURES



## LAMPING

It brings power directly above a MonoRail run from a remote transformer (sold separately). The low-voltage leads from the remote transformer are connected to the canopy leads inside the junction box. Compatible with MonoRail 1" Rigid Standoff. Not compatible with Power Extenders nor Power Vault Adapter.

MonoRail 4" Round Power Feed Canopy Low-Profile Dual-Feed



MonoRail 4" Round  
Power Feed  
Canopy Low-Profile  
Dual-Feed

## ORDERING INFORMATION

700MOP4C401 FINISH

S SATIN NICKEL

700MOP4C401 \_\_\_\_\_

JOB NAME \_\_\_\_\_

NOTES \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_




# MONORAIL 4" ROUND POWER FEED CANOPY LOW-PROFILE DUAL-FEED



## SPECIFICATIONS

HARDWARE MATERIAL
SHADE MATERIAL
NET WEIGHT
HEIGHT
WIDTH
LENGTH
WET LISTED
DAMP LISTED
DRY LISTED
GENERAL LISTING
INCLUDES



## LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS				
WATTS				
MAX WATTAGE PER BULB				
INPUT VOLTAGE				
DIMMING TYPE*				
CCT				
CRI				
LED LIFETIME				
L70				
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE				
LAMP SHAPE				
LAMP INCLUDED?				
WARRANTY**				

\* Dimming information available at [www.techlighting.com/Downloads#dimming](http://www.techlighting.com/Downloads#dimming)  
 \*\* Visit [techlighting.com](http://techlighting.com) for specific warranty limitations and details.

## T20 / T24 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 <b>Title 24</b> Part 6.			
This product can be used to comply with California Appliance Efficiency Standards 2016 <b>Title 20</b> and may be shipped to and sold in California.			

\* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

