


MONORAIL REMOTE KIT 300W




PRODUCT FEATURES



LAMPING

Installs in an accessible location behind the ceiling or wall. Mounts to a standard 4" junction box. Rail drops 2" from ceiling. Add up to six 50 watt elements or up to eight 35 or 37 watt fixture depending on lamp type.

MonoRail Remote Kit 300w



ORDERING INFORMATION

700MOKTA300 FINISH

- R AGED BRASS
- Z ANTIQUE BRONZE
- S SATIN NICKEL

700MOKTA300 _____

JOB NAME _____

NOTES _____



MONORAIL REMOTE KIT 300W



SPECIFICATIONS

HARDWARE MATERIAL	
SHADE MATERIAL	
NET WEIGHT	
HEIGHT	20in
WIDTH	12in
LENGTH	
WET LISTED	
DAMP LISTED	
DRY LISTED	
SLOPED CEILING ADAPTABLE?	No
GENERAL LISTING	ETL Listed
INCLUDES	

LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS				
WATTS				
MAX WATTAGE PER BULB			300W	
INPUT VOLTAGE			120V	
DIMMING TYPE*				
CCT				
CRI				
LED LIFETIME				
L70				
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE				
LAMP SHAPE				
LAMP INCLUDED?			Y	
WARRANTY**				

*Dimming information available at www.techlighting.com/Downloads#dimming

** Visit techlighting.com for specific warranty limitations and details.

T20 / T24 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6.			
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.			

* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

