CROSSROADS PENDANT

TECH LIGHTING

PRODUCT FEATURES

- · Composed of raw sheet steel
- · Clear lacquer coat to protect finish
- Beautiful brass spot welding accents sleek sheet metal
- Complementary Crossroads linear suspension and wall mount also available by Tech Lighting
- Ships with halogen or replaceable SORAA® LED module included to save you time and money
- Protected by a 1-year warranty



LAMPING

Includes low-voltage, 50 watt halogen bi-pin lamp or 6 watt, 300 delivered lumen, 3000K, replaceable Tech Lighting LED module and six feet of field-cuttable cable. Dimmable with low-voltage electronic or magnetic dimmer (based on transformer).



ORDERING INFORMATION

| 700 | SYSTEM | CRS | FINISH | LAMP | |
|-----|--------------------|-----|------------------------|---|-----------------------|
| | FJ FREEJACK | | Z STEEL/ANTIQUE BRONZE | | 12 VOLT HALOGEN (T20) |
| | MP MONOPOINT | | S STEEL/SATIN NICKEL | -24 | 24 VOLT HALOGEN |
| | MO MONORAIL | | | -LEDS930 12 VOLT LED 90 CRI 3000K (T20/T24) | |
| | | | | -24 | 24 VOLT HALOGEN |

Note: MP includes 4" Round Flush Canopy and is available in 120v only (for 277v order as FJ).

| 700 | CRS | | |
|----------|-----|--|--|
| JOB NAME | | | |
| NOTES | | | |
| | | | |




CROSSROADS PENDANT

TECH LIGHTING

SPECIFICATIONS

| HARDWARE MATERIAL | Metal |
|-------------------------------|-------------|
| SHADE MATERIAL | Metal |
| NET WEIGHT | 2.13 lbs |
| HEIGHT | 10.4in |
| WIDTH | 3.5in |
| LENGTH | 3.5in |
| UP LIGHT / DOWN LIGHT / BOTH? | |
| WET LISTED | |
| DAMP LISTED | |
| DRY LISTED | |
| MIN. HANGING HEIGHT | 10.4in |
| MAX HANGING HEIGHT | 82.9in |
| SLOPED CEILING ADAPTABLE? | Yes 45° Max |
| GENERAL LISTING | ETL Listed |
| INCLUDES | |



LAMPING SPECIFICATIONS

| | LED LAMP | INTEGRATED LED | NON LED | NO LAMP |
|-----------------------|-------------|----------------|---------|---------|
| DELIVERED LUMENS | 300 | | | |
| WATTS | 8 | | | |
| MAX WATTAGE PER BULB | 50W | | 50W | |
| INPUT VOLTAGE | 12V | | 12V | |
| INPUT VOLTAGE | 120V | | 120V | |
| DIMMING TYPE* | ELV | | ELV | |
| ССТ | 3000K-1800K | | | |
| CRI | 90 CRI | | | |
| LED LIFETIME | | | | |
| L70 | 25000 | | | |
| AVERAGE BULB HOURS | 25000 | | | |
| FIELD SERVICEABLE LED | | | | |
| LAMP BASE | GU5.3 | | GU5.3 | |
| LAMP SHAPE | ВП5 | | ВП5 | |
| LAMP INCLUDED? | Υ | | Υ | |
| WARRANTY** | 1 Year | | 1 Year | |

 $^{* \}texttt{Dimming information available at} \ \underline{www.techlighting.com/Downloads\#dimming}$

T20 / T24 INFORMATION

| | Integrated LED | Replacement LED Lamp | No Lamp * |
|--|-------------------|-------------------------|--------------|
| This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6. | | Yes | N/A |
| This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to anc sold in California. | | Yes | N/A |

 $^{^*}$ If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.



^{**}Visit techlighting.com for specific warranty limitations and details.