

FINCH ROUND FLUSH MOUNT

PRODUCT FEATURES

- Modern clean lined flush mount fixture
- Minimalist design style
- Available in both round and square shape profiles
- Finch Flush Mount also available from Tech Lighting
- Ideal for hallways, bathrooms and bedrooms
- 5 year warranty with LED lamping



LAMPING

Includes 29 watt, 1152 delivered lumen, 80 CRI, 3000K LED. 120V and 277V dimmable with most LED compatible ELV and TRIAC dimmers. Can be wall or ceiling mounted.

Satin Nickel
Round



Antique Bronze
Round

Satin Nickel
Round

ORDERING INFORMATION

700FMFIN	SHAPE OR SIZE	FINISH	LAMP
	R ROUND	Z ANTIQUE BRONZE S SATIN NICKEL	-LED830 LED 3000K 80 CRI 120V -LED830-277 LED 3000K 80 CRI 277V

700FMFIN _____

JOB NAME _____


NOTES _____



FINCH ROUND FLUSH MOUNT

SPECIFICATIONS

HARDWARE MATERIAL	Metal
SHADE MATERIAL	Glass
NET WEIGHT	5 lbs
HEIGHT	2.1in
WIDTH	12in
LENGTH	12in
UP LIGHT / DOWN LIGHT / BOTH?	
WET LISTED	
DAMP LISTED	Yes
DRY LISTED	
WALL / CEILING MOUNT	
GENERAL LISTING	ETL Listed
INCLUDES	



LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS		1152		
WATTS		29		
MAX WATTAGE PER BULB		29W		
INPUT VOLTAGE		120V 277V		
DIMMING TYPE*		ELV, TRIAC		
CCT		3000K		
CRI		80 CRI		
LED LIFETIME				
L70		>50000		
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE		Integrated LED		
LAMP SHAPE		Integrated LED		
LAMP INCLUDED?		Y		
WARRANTY**		5 Years		

* Dimming information available at www.techlighting.com/Downloads#dimming

** Visit techlighting.com for specific warranty limitations and details.

T20 / T24 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6.	No		
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.	N/A		

* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

