


## PRODUCT FEATURES



## LAMPING

Two common uses are in runs using more than 300w or in runs over 30ft where two power feeds are required to avoid voltage drop. All dual-feed canopies and dual-feed surface transformers are shipped with isolating connectors; order additional if required by layout. Pair.

MonoRail Isolating Connectors



MonoRail Isolating Connectors

## ORDERING INFORMATION

700MOCINC

---

700MOCINC \_\_\_\_\_

JOB NAME \_\_\_\_\_


NOTES \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_



# MONORAIL ISOLATING CONNECTORS

## SPECIFICATIONS

HARDWARE MATERIAL	
SHADE MATERIAL	
NET WEIGHT	0.01 lbs
HEIGHT	0.3in
WIDTH	1.1in
LENGTH	1.1in
WET LISTED	
DAMP LISTED	
DRY LISTED	
GENERAL LISTING	ETL Listed
INCLUDES	



## LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS				
WATTS				
MAX WATTAGE PER BULB				
INPUT VOLTAGE			0V	
DIMMING TYPE*				
CCT				
CRI				
LED LIFETIME				
L70				
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE				
LAMP SHAPE				
LAMP INCLUDED?				
WARRANTY**			1 Year	

\*Dimming information available at [www.techlighting.com/Downloads#dimming](http://www.techlighting.com/Downloads#dimming)  
 \*\* Visit [techlighting.com](http://techlighting.com) for specific warranty limitations and details.

## T20 / T24 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 <b>Title 24</b> Part 6.			N/A
This product can be used to comply with California Appliance Efficiency Standards 2016 <b>Title 20</b> and may be shipped to and sold in California.			N/A

\* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

