

PAR LOUVER LENS HOLDER

PRODUCT FEATURES



LAMPING

MR16/PAR16 size holds one lens or louver; PAR20, PAR30 and PAR38 sizes hold up to two lenses or louvers (sold separately). Lamps not included. Line-Voltage PAR16 GU10 lamp up to 50 watts. Line-Voltage CMH MR16 lamp up to 39 watts. Line-Voltage PAR20 lamp up to 50 watts. Line-Voltage CMH PAR20 lamp up to 39 watts. Line-Voltage PAR30 lamp up to 75 watts. Line-Voltage CMH PAR30 Long lamp up to 70 watts. Line-Voltage PAR38 lamp up to 120 watts.

PAR Louver Lens Holder

ORDERING INFORMATION

700PARLL	SHAPE OR SIZE	FINISH
	16 MR16/PAR16	S SATIN NICKEL
	20 PAR20	
	30 PAR30	

700PARLL _____

JOB NAME _____

NOTES _____



SPECIFICATIONS

PRIMARY MATERIAL	
SHADE MATERIAL	
NET WEIGHT	0.1 lbs
HEIGHT	3.75in
WIDTH	0.1in
LENGTH	
WET LISTED	
DAMP LISTED	
DRY LISTED	
GENERAL LISTING	ETL Listed
INCLUDES	

LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS				
WATTS				
MAX WATTAGE PER BULB				
INPUT VOLTAGE/ DIMMING TYPE				
CCT				
CRI				
LED LIFETIME				
L70				
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE				
LAMP SHAPE				
LAMP INCLUDED?				
WARRANTY**				

* Dimming information available at www.techlighting.com/Downloads#dimming
 ** Visit techlighting.com for specific warranty limitations and details.

T20 / T24 / JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6 / JA8.			N/A
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.			N/A

* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

