

# ISO HEAD

## PRODUCT FEATURES

- Sleek and contemporary design combined with lighting precision
- Wide range of beam spreads, 20°, 30° or 50°
- Complementray Monorail or Monopoint systems by Tech Lighting
- Available in modern finishes
- Ideal for commercial and residential lighting applications
- Protected by a 5-year warranty



Aged Brass

## LAMPING

Includes 16 watt, 704.1 delivered lumens, 3000K, 90 CRI field replaceable LED module. Dimmable to 10% dimmer type determined by low-voltage transformer. The heat sink remains with the fixture minimizing any waste at the end of the lamp module's life. The head rotates 360° and pivots 90° to direct the beam. As a general rule when using the ISO Head, we do not recommend using greater than 33% of the maximum wattage specified for the low-voltage transformer due to the inrush current requirements. For assistance in calculations, please contact our Technical Support Department.



Satin Nickel

White

Aged Brass

## ORDERING INFORMATION

700	SYSTEM	ISO	CRI	COLOR TEMP	BEAM SPREAD	LENGTH (A)	FINISH	LAMP
	FJ FREEJACK	8	80 CRI	27 2700K	20 20°	03 3"	R AGED BRASS	-LED LED
	MP MONOPOINT	9	90 CRI	30 3000K	30 30°	06 6"	S SATIN NICKEL	
	MO MONORAIL				50 50°	12 12" 18 18"	W WHITE	

2700K not available with 90 CRI

MP includes 4" Round Flush Canopy.

Due to weight capacity issues, do not exceed a 45 degree angle. For custom stem lengths, please contact the Quotes Department.

700 \_\_\_\_\_ ISO \_\_\_\_\_


JOB NAME \_\_\_\_\_

NOTES \_\_\_\_\_



## SPECIFICATIONS

HARDWARE MATERIAL	Metal
SHADE MATERIAL	
NET WEIGHT	1.58 lbs
HEIGHT	3.6in
WIDTH	2.8in
LENGTH	3.6in
BEAM SPREAD	
UP LIGHT / DOWN LIGHT / BOTH?	
WET LISTED	
DAMP LISTED	
DRY LISTED	
MIN. HANGING HEIGHT	3in
MAX HANGING HEIGHT	3in
TOTAL CORD LENGTH	
SLOPED CEILING ADAPTABLE?	No
GENERAL LISTING	ETL Listed
INCLUDES	



## LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS	704.1	704.1		
WATTS	16	16		
MAX WATTAGE PER BULB	16W	16W		
INPUT VOLTAGE	120V 12V	120V 12V		
DIMMING TYPE*	ELV	ELV		
CCT	2700K 3000K	2700K 3000K		
CRI	80 CRI 90 CRI	80 CRI 90 CRI		
LED LIFETIME				
L70	50000	50000		
AVERAGE BULB HOURS	50000	50000		
FIELD SERVICEABLE LED				
LAMP BASE	Integrated LED	Integrated LED		
LAMP SHAPE	Integrated LED	Integrated LED		
LAMP INCLUDED?	True	True		
WARRANTY**	5 Years	5 Years		

\*Dimming information available at [www.techlighting.com/Downloads#dimming](http://www.techlighting.com/Downloads#dimming)

\*\* Visit [techlighting.com](http://techlighting.com) for specific warranty limitations and details.

## T20 / T24 / JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 <b>Title 24</b> Part 6 / <b>JA8</b> .	Yes		
This product can be used to comply with California Appliance Efficiency Standards 2016 <b>Title 20</b> and may be shipped to and sold in California.	N/A		

\* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

