

SPHERE FLUSH MOUNT

PRODUCT FEATURES

- A beautiful spherical glass shade nested with a clean and modern back-plate
- Mount as a wall sconce or flush mount
- Sphere Flush Mounts are a great way to illuminate a hallway or add a touch of elegance to your space
- Protected by a 5-year warranty with integrated LED



LAMPING

LED includes 14.4 watt 579 lumen 90 CRI warm color dimming 3000K-2200K LED module. Dimmable with a standard incandescent dimmer or low-voltage electronic dimmer. May also be mounted as a wall sconce. ADA compliant.

Clear



Clear

ORDERING INFORMATION

700FMSPH	COLOR	FINISH	LAMP
	C CLEAR	S SATIN NICKEL	-LEDWD INTEGRATED LED 90 CRI 3000-2200K 120V

700FMSPH _____


JOB NAME _____

NOTES _____



SPHERE FLUSH MOUNT

SPECIFICATIONS



PRIMARY MATERIAL	Glass
SHADE MATERIAL	
NET WEIGHT	3 lbs
HEIGHT	3in
WIDTH	4.7in
LENGTH	4.7in
UP LIGHT / DOWN LIGHT / BOTH?	
WET LISTED	
DAMP LISTED	Yes
DRY LISTED	
WALL / CEILING MOUNT	
GENERAL LISTING	ETL Listed
INCLUDES	

LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS		579.0		
WATTS		14.4		
MAX WATTAGE PER BULB		14.4W		
INPUT VOLTAGE/ DIMMING TYPE		120V ELV, TRIAC		
CCT		3000K-2200K		
CRI		90 CRI		
LED LIFETIME		>50000		
L70				
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE		Integrated LED		
LAMP SHAPE		Integrated LED		
LAMP INCLUDED?		True		
WARRANTY**		5 Years		

* Dimming information available at www.techlighting.com/Downloads#dimming
 ** Visit techlighting.com for specific warranty limitations and details.

T20 / T24 / JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6 / JA8.	No		
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.	N/A		

* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

