

PRODUCT FEATURES

- Die-cast aluminum structure, powder coat finish, and stainless steel hardware for robust durability in harsh elements. Appropriate for commercial use.
- Recessed LED to minimize glare
- Downlight only
- Universal 120-277 volt driver.
- IP65 Wet Rated
- Protected by a 5-year warranty. Please visit the "About Us" Page on techlighting.com for more for warranty details



LAMPING

Black
3/4 View



Black

Black
3/4 View

ORDERING INFORMATION

7000WLYD CRI	COLOR TEMP	LENGTH (A)	FINISH	VOLTAGE
9 90 CRI	30 3000K	5 5"	B BLACK	UNV UNIVERSAL 120V-277V

7000WLYD _____

JOB NAME _____

NOTES _____




LLOYDS 5 OUTDOOR WALL



SPECIFICATIONS

PRIMARY MATERIAL	Aluminum
SHADE MATERIAL	Aluminum
NET WEIGHT	
HEIGHT	4.5in
WIDTH	2.6in
LENGTH	4.5in
WET LISTED	Yes
DAMP LISTED	
DRY LISTED	
GENERAL LISTING	ETL Listed
INCLUDES	



LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS		1090		
WATTS		10		
MAX WATTAGE PER BULB				
INPUT VOLTAGE/ DIMMING TYPE		Universal 120V-277V 0-10, ELV, TRIAC		
CCT		3000K		
CRI		90 CRI		
LED LIFETIME				
L70		>60000		
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE		Integrated LED		
LAMP SHAPE		Integrated LED		
LAMP INCLUDED?		True		
WARRANTY**		5 Years		

* Dimming information available at www.techlighting.com/Downloads#dimming

** Visit techlighting.com for specific warranty limitations and details.

T20 / T24 / JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6 / JA8.	Yes		
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.			

* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

