

# FREEJACK SQUARE CANOPY 4-PORT LED

## PRODUCT FEATURES



## LAMPING

Electronic transformers inside an 11" by 11" housing. Four FreeJack ports; for ceiling only.

FreeJack Square Canopy 4-port LED



FreeJack Square Canopy 4-port LED

## ORDERING INFORMATION

700FJS4	SHAPE OR SIZE	FINISH	VOLTAGE
	SQUARE 4 PORT INTEGRAL TRANSFORMER	S SATIN NICKEL	-LED 120V IN/12V OUT LED -LED277 277V IN/12V OUT LED

For use with any four 12 Volt LED FreeJack pendants (sold separately). Consult factory for use with 12 volt LED FreeJack Heads.

700FJS4

JOB NAME

NOTES




# FREEJACK SQUARE CANOPY 4-PORT LED



## SPECIFICATIONS

HARDWARE MATERIAL
SHADE MATERIAL
NET WEIGHT
HEIGHT
WIDTH
LENGTH
WET LISTED
DAMP LISTED
DRY LISTED
GENERAL LISTING
INCLUDES



## LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS				
WATTS				
MAX WATTAGE PER BULB				
INPUT VOLTAGE				
DIMMING TYPE*				
CCT				
CRI				
LED LIFETIME				
L70				
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE				
LAMP SHAPE				
LAMP INCLUDED?				
WARRANTY**				

\*Dimming information available at [www.techlighting.com/Downloads#dimming](http://www.techlighting.com/Downloads#dimming)  
 \*\* Visit [techlighting.com](http://techlighting.com) for specific warranty limitations and details.

## T20 / T24 / JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 <b>Title 24</b> Part 6 / <b>JA8</b> .			
This product can be used to comply with California Appliance Efficiency Standards 2016 <b>Title 20</b> and may be shipped to and sold in California.			

\* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

