

KABLE LITE UNIVERSAL TURNBUCKLES



PRODUCT FEATURES



LAMPING

For long or turning runs (runs over 20'). Mount to wall or ceiling. When ceiling mounted, cables drop 2.5" from ceiling. Pair. 2" Minimum Cable Separation. If mounting to metal, order isolating connector (sold separately).

Kable Lite Universal Turnbuckles



Kable Lite
Universal
Turnbuckles

ORDERING INFORMATION

700PART	LENGTH (A)	FINISH
	2.5"	S SATIN NICKEL

700PART _____

JOB NAME _____

NOTES _____




KABLE LITE UNIVERSAL TURNBUCKLES



SPECIFICATIONS

HARDWARE MATERIAL	
SHADE MATERIAL	
NET WEIGHT	0.85 lbs
HEIGHT	2.5in
WIDTH	1.8in
LENGTH	2.5in
WET LISTED	
DAMP LISTED	
DRY LISTED	
GENERAL LISTING	ETL Listed
INCLUDES	



LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS				
WATTS				
MAX WATTAGE PER BULB				
INPUT VOLTAGE			0V	
DIMMING TYPE*				
CCT				
CRI				
LED LIFETIME				
L70				
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE				
LAMP SHAPE				
LAMP INCLUDED?				
WARRANTY**			1 Year	

*Dimming information available at www.techlighting.com/Downloads#dimming
 ** Visit techlighting.com for specific warranty limitations and details.

T20 / T24 / JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6 / JA8 .			N/A
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.			N/A

* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

